

## MPT-200 E MPT-500 WITHOUT RESERVOIR

### Technical Features

DISCHARGE/MINUTE	100 CC O 500 CC
WORKING PRESSURE	5 - 25 bar (70-354 PSI) ADJUSTABLE 15-50 bar (212-708 PSI) ADJUSTABLE
RELEASE VALVE	0.7 bar
SUCTION STRAINER	250 O 400 MICRON
PRESSURE GAUGE	0 - 60 bar / 0 - 870 PSI
DISCHARGE PORT	M12X1 TUBE 6mm
TEMPERATURE RANGE	FROM -20°C TO +80°C
LUBRICANTS	OIL 50 - 1000 cSt 40°C SOFT GREASE NLGI 000 - 00
LOW LEVEL SWITCH CAPACITY LOW LEVEL SWITCH	1.5 A 250 V AC 200 V DC 50 W FROM 10 V TO 40 V DC
MOTOR	SEE TABLE AT PAGE 20



### Codes For Order

CODE	PRESSURE	TYPE	RESERVOIR CAPACITY	TYPE	PRESSURE	CODE
60.825.2	5 - 25 bar	MPT-500 S/S O 145	60.826.5	MPT-500 S/S G 240	15 - 50 bar	60.822.2
60.825.3	5 - 25 bar	MPT-500 S/S O 240	60.825.0	MPT-200 S/S O 145	5 - 25 bar	60.822.3
60.825.4	15 - 50 bar	MPT-500 S/S O 145	60.825.1	MPT-200 S/S O 240	5 - 25 bar	60.822.7
60.825.5	15 - 50 bar	MPT-500 S/S O 240	60.826.0	MPT-200 S/S G 145	15 - 50 bar	60.822.3
60.826.4	15 - 50 bar	MPT-500 S/S G 145	60.826.1	MPT-200 S/S G 240	15 - 50 bar	60.822.7
60.822.1	5 - 25 bar	MPT-6-NY-500-25	6 L NYLON	MPT-6-NY-500-50	15 - 50 bar	60.822.3

On request can be supplied special motor voltages or single phase 115 v – 230 v ac 50/60hz. In this case add the voltage to the order code.

### Overall Dimension

PUMP	H	BAR	PUMP	H	BAR
MPT-500 S/S O	145	5 - 25 bar	MPT-500 S/S G	240	15 - 50 bar
MPT-500 S/S O	240	5 - 25 bar	MPT-200 S/S O	145	5 - 25 bar
MPT-500 S/S O	145	15 - 50 bar	MPT-200 S/S O	240	5 - 25 bar
MPT-500 S/S O	240	15 - 50 bar	MPT-200 S/S G	145	15 - 50 bar
MPT-500 S/S G	145	15 - 50 bar	MPT-200 S/S G	240	15 - 50 bar

