

## SOFT GREASE MPT-500/G/LAM ELECTRIC PUMP

These pumps can be used in medium-big machines with a large points number.

### Technical Features

DISCHARGE/MINUTE	500 CC
WORKING PRESSURE	5 - 25 bar (70-354 PSI) ADJUSTABLE
RELEASE VALVE	0.7 bar
RESERVOIR	8 L - 12 L - 50 L
SUCTION STRAINER	400 MICRON
PRESSURE GAUGE	0 - 60 bar / 0 - 870 PSI
DISCHARGE PORT	M12X1 TUBE 6mm
TEMPERATURE RANGE	FROM -20°C TO +80°C
LUBRICANTS	SOFT GREASE NLGI 000 - 00
LOW LEVEL SWITCH	FROM 10 V TO 40 V DC
MOTOR	SEE TABLE AT PAGE 20



### Codes For Order

CODE	PRESSURE	TYPE	RESERVOIR CAPACITY
60.824.8	15 - 50 bar	MPT-6-G-LA-500-50	8 L
60.824.9	15 - 50 bar	MPT-12-G-LA-500-50	12 L
60.829.3	15 - 50 bar	MPT-50-G-LA-500-50	50 L

On request can be supplied special motor voltages or single phase 115 v - 230 v ac 50/60hz. In this case add the voltage to the order code.

### Overall Dimension

PUMP	A	B	C	D	E	F	WEIGHT
MPT-6-G-LA	250	205	430	305	173	330	10 KG
MPT-12-G-LA	250	205	430	330	196	355	12 KG
MPT-50-G-LA	400	300	580	530	270	560	18 KG

