

PRA-30/35/G/LAM SOFT GREASE PNEUMATIC PUMP

Technical Features

DISCHARGE/CYCLE	13 CC
WORKING PRESSURE	30 bar (425 PSI) MAX
RATIO	4.5 ÷ 1
AIR OPERATING PRESSURE	FROM 4 bar TO 7 bar
	FROM 60 PSI TO 100 PSI
RELEASE VALVE	0.7 bar (10 PSI)
CYCLES NUMBER/MINUTE	MAX 4
METALLIC RESERVOIR	8 L – 12 L
SUCTION STRAINER	250 MICRON
PRESSURE GAUGE	0-60 bar / 0-850 PSI
DISCHARGE PORT	M12x1 - TUBE 6 MM
TEMPERATURE RANGE	FROM - 10°C TO + 80°C
LUBRICANTS	SOFT GREASE NLGI 000 - 00
LOW LEVEL SWITCH	10 A TO 40 V DC
AIR INLET	1 / 4" G



Codes For Order

CODE	TYPE	RESERVOIR CAPACITY
00.226.7	PRA-30-G LAM	8 L
00.226.8	PRA-35-G LAM	12 L

Overall Dimension

PUMP	A	B	C
PRA-30-G LA	305	330	165
PRA-35-G LA	330	355	198

