Product Information



Xport[™] Lubricant Application

Xport™ Clear Grease Gun

Reliability tool helps eliminate maintenance errors.



Human error in maintenance does happen; the wrong grease is applied to a piece of equipment, leading to crosscontamination and worse yet, critical bearing and equipment failure. Such maintenance errors or malpractice can be very costly and time-consuming to correct. Say goodbye to grease-related servicing errors by upgrading to the Xport[™] Clear Grease Gun solution. This reliability tool is helping organizations worldwide enhance their operations' reliability maintenance efforts, enhancing overall accountability and safety.

Beneficial Qualities

- Allows 100% visual identification
- Eliminates cross-contamination
- Enhances existing reliability programs

Clearly Reliable

- Tubes are capable of withstanding heavy use and high temperatures.
- Collars and caps available in multiple colors – are durable anodized aluminum and will not rust.
- Guns are available in pistol grip and lever styles.



Asset Reliability Solutions™

413-788-5823





Xport™ Clear Grease Gun

	Pistol Grip (619LE)	<u>Lever Style (HD4LE)</u>
Maximum pressure	5,000 psi	10,000 psi
Grease delivery	1-oz per 40 strokes	1-oz per 28 strokes
Includes whip hose	12"	12"
Includes hard pipe extension	4"	6"
Grease gun head material type	Aluminum cast head	Aluminum cast head
Holds grease cartridge	14½ oz	14½ oz
Loader nipple	Optional	Included
Recommended for grease up to	NLGI 2	NLGI 2
Multiple loading	Via cartridge, suction or bulk	Via cartridge, suction or bulk
Operation	Comfortable one-hand	Variable stroke
NPT Threads	1/8"	1/8"
Warranty	2-year gun warranty	2-year gun warranty

Xport[™] Clear Grease Tubes

- Available for purchase separately
- High-impact, fracture-resistant polycarbonate
- Tube thread pattern: 2.280-16 UNS-non-standard
- Fit many common grease gun models, including:
 - Lincoln[®], Alemite[®] and Plews[®] guns
 - Alemite** Model Series 500, 590, 525
 - Lincoln 1133, 1132, 1134*, 1142, 1145, 1147, 1148
 - Zeeline 444, 610, 613, 619, 620, HD4, HD4A
- Durable T6061 aircraft aluminum collars
- Variety of collar colors available for secondary identification, including: silver, gold, purple, blue, black, red, green


Clear Grease Tubes with Color Options

*May not fit with older 1134 models. **Physical confirmation of fit will be necessary.

Xport™ Lock-On Grease Coupler

Makes greasing tasks easy, clean, safe & fast!

This optional accessory for LE's Clear Grease Guns is a durable jaws-free device that eases grease fitting coupling and uncoupling. It includes five retaining balls to ensure a proper seal between fitting and pump.



- Carbon and stainless steel components
- Smooth push mechanism easily locks coupler to grease fitting
- Max. pressure: 10,000 psi (700 bar)
- Weight: 0.09 pounds (40 g)
- Inlet thread: 1/8" NPT female



Xport[™] is a trademark of Lubrication Engineers, Inc. Lincoln[®] is a registered trademark of Lincoln Industrial Corp. Alemite[®] is a registered trademark of Alemite. Plews[®] is a registered trademark of Plews/Edelmann.

A00048 12-10, rev. 11-17

413-788-5823